

#### LED WALLPACK MINI ST-WPMNV1

### **PRODUCT DESCRIPTION**

The LED Wallpack Mini is a compact outdoor light designed to offer upto 135 Lumens per Watt, and is suitable for Wet locations. This light is an ideal solution for illuminating property entrances, walkways, outdoor landscape lighting, building walls and a variety of other outdoor architectural applications.

# **KIT INFORMATION**

Finish: Bronze Mounting: Surface Mounting Dimensions: 8.60" x 5.70" x 3.00"

## **FEATURES**

Energy efficient LED light engine offers high lumen output as well as high efficacy

Compact design with architectural look

Easy to install

IP65 Rated

5 Year Warranty

#### PERFORMANCE RATINGS AND CERTIFICATIONS

ETL, cETL, DLC

### PERFORMANCE SUMMARY

Lumens: 2500 - 2850 lumens Lumens per Watt: 125-135 lm/W CRI-Minimum: >80 CCT: Cool White (5000K) Watts: 20W Operating Environment: -20°C to 40°C Optical Distribution: 100° Viewing Angle

## ELECTRICAL SYSTEM CHARACTERIZATIONS

Voltage: 120 - 277VAC, 50/60 Hz Dimming: Power Factor: >0.9 Total Harmonic Distortion: ≤ 20%

# WARRANTY

5 Year Standard Warranty Limited

Specifications are subject to change at any time without notice. For more information and product support, contact GenPro Advanced Technologies at 800.465.1286 or email info@GenProTech.com

Copyright GenPro Advanced Technologies

### www.GenProTech.com





#### **ORDERING MATRIX**

**Example:** ST-WPMNV1-20W-CW-MT

Family	Product	Color Temp	Voltage	Options
ST	WPMNV1-20W = LED Wallpack Mini 20W	CW = Cool White (5000K)	MT = 120-277VAC 50/60 Hz	Photocell is included

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






#### AVERAGE BEAM ANGLE (50%):

98.7 DEG — C0/180 102.3

— C90/270 95.0



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.