

PRODUCT DESCRIPTION

The LED Center-Basket Troffer is an ideal substitute for traditional florescent tube troffers offering over 60% energy savings. This troffer offers a high efficacy of upto 125 lumens/ Watt. Suitable for: office spaces, commercial, retail and a variety of other indoor applications.

FEATURES

• 60% less energy consumption than traditional

troffers

- High efficacy: 125 lumens/Watt
- 0-10V Dimming
- 5 Year Warranty

PERFORMANCE RATINGS AND CERTIFICATIONS

UL, DLC

PERFORMANCE SUMMARY

Lumens: 3750 (30W), 5000 (40W) Lumens per Watt: 125 CRI-Minimum: >80 CCT: Cool White (5000K), Natural White (4000K) Watts: 30W, 40W Operating Environment: -25°C to 40°C

Optical Distribution: 150° Beam Angle





KIT INFORMATION

Finish: White frame Mounting: Recessed Dimensions: 23.70" x 23.70" x 3.62"

ELECTRICAL SYSTEM CHARACTERIZATIONS

Voltage: 120 - 277VAC, 50/60 Hz Dimming: 0-10V dimming Power Factor: ≥0.9 Total Harmonic Distortion: <20%

WARRANTY

5 Year Standard Warranty Limited

Specifications are subject to change at any time without notice. For more information and product support, contact GenPro Advanced Technologies at 800.465.1286 or email info@GenProTech.com

Copyright GenPro Advanced Technologies

www.GenProTech.com



ORDERING MATRIX

Example: ST-TR22V1-30W-CW-MT-MS

Family	Product	Watts	Color Temp	Voltage	Options
ST	TR22V1 = LED Center-Basket Troffer 2 x 2	30W 40W	CW = Cool White (5000K) NW = Natural White (4000K)	MT = 120-277VAC 50/60 Hz	None (Leave Blank) MS = Internal Motion Sensor

PRODUCT DIMENSIONS

